

Comparison table of all automatic dial, alert and alarm systems

Feature	I-TEL 2+	I-TEL 2+ IP ISDN	I-TEL 3 IP	I-TEL 3L	I-TEL 3
Telephone net	analogue	ISDN	analogue	analogue	analogue
use on PABX possible	yes	yes	yes	yes	yes
dial system	tone	tone	tone	tone	tone
amount of alarm lines	1	1	4	2	4
alarm line as opener	yes	yes	yes	yes	yes
alarm line as closer	yes	yes	yes	yes	yes
alarm line differential	no	no	yes	yes	yes
additional alarm line for recognition of power supply loss and alert function	no	no	yes	yes	yes
amount of telephone numbers	4	4	8	8	8
length of telephone numbers	20	20	20	20	20
length of digital prerecorded voice message	35	35	60	60	60
confirmation of received messages by voice	yes	yes	yes	yes	yes
confirmation of received messages by tax metering impulse	yes	yes	yes	yes	yes
confirmation of received messages by tone dial	no	no	yes	yes	yes
dialing of additional numbers after reception cancelable	yes	yes	yes	yes	yes
aktive states (eg. day and night or at home and not at home)	1	1	2	1	2
Switching relay (rc or program controled)	no	no	yes, 2 pieces	no	yes, 2 pieces
logging function	yes	yes	yes	yes	yes
activity surveilance	no	no	yes	yes	yes
LC-Display	1×16 chars.	1×16 chars.	2×16 chars.	2×16 chars.	2×16 chars.
keypad 16 keys	yes	yes	yes	yes	yes
internal mikrophone and loudspeaker	yes	yes	yes	yes	yes
power supply	230 V ~	230 V ~	approx. 12 V ~= V ~=	approx. 12 V ~= V ~=	approx. 12 V ~= V ~=
rc set	optional	optional	optional	optional	optional
emergency power supply (UPS)	optional	internal	internal	optional	optional
PC-adapter and PC-software	no	no	optional	optional	optional
enclosure for easy wall mounting	yes	yes	yes	yes	yes
enclosure according IP 56	no	yes	yes	no	no
weight approx.	450 g	2300 g	2200 g	450 g	450 g
europaean wide approval (CE approval)	yes	yes	yes	yes	yes